

# PERFETTO VACUUM MODULE WITH INVERTER

## with automatic regulation

The **PERFETTO vacuum modules** are designed to work based on the number of operators at the same time and on large surface areas.

These modules are equipped with **INVERTER** with electronic pressure regulation and **SOFT START** engine start.

The vacuum modules are **soundproofed** and equipped with a **digital display** that indicates the operating status of the turbine.

Each vacuum modules can be associated with multiple **interconnected vacuum modules**, to ensure the cleaning needs of the most complex structures (hotels, residences, healthcare, commercial or industrial facilities).



## Complementary Accessories for Vacuum modules

**CI380 - Ø80 metal silencer**  
dimensions: h 70 cm x Ø17 cm

**CI390 - Ø100 metal silencer**  
dimensions: h 70,5 cm x Ø20 cm

**CI397 - Ø160 metal silencer**  
dimensions: h 90,5 cm x Ø22 cm



### Optional accessory

Metal silencers are supplied with a rubber sleeve and metal clamps for connection to the air exhaust line.

**CI581 - Check valve for T30INV**

**CI591 - Check valve for T40INV - T60INV**



### Optional accessory

The valves are supplied with a rubber sleeve and metal clamps for connection.

**CI320 - Ø 63 compensation valve**

**CI325 - Ø 80 compensation valve**

**CI340 - Ø 100 compensation valve**



### Optional accessory

The compensation valve ensures the regular air intake value.

Perfetto vacuum modules AUTOMATIC REGULATION WITH INVERTER				
Models		T30INV	T40INV	T60INV
Commercial code		CI426	CI436	CI446
Operators at the same time	n°	3	4	6
Vacuum module power supply	V	380/400	380/400	380/400
Maximum absorption	A	8	11	15
Frequency	Hz	50/60	50/60	50/60
Motor rpm	rpm	3.500	3.500	3.500
Motor power	W	4.800	6.500	9.000
Soft Start		Yes	Yes	Yes
Inverter		Yes	Yes	Yes
System vacuum regulation		Automatic	Automatic	Automatic
Maximum pressure	mbar	450	490	490
Air flow rate	m <sup>3</sup> /h	650	800	950
Vacuum sockets power supply	V	12	12	12
Soundproofing		Yes	Yes	Yes
Noise	dB	<70	<73	<74
Air inlet diameter	mm	100	100	100
Air exhaust outlet diameter	mm	100	100	100
Diameter vacuum modules	cm	66	66	66
Hight vacuum modules	cm	95	95	95
Weight	kg	73	86	95

### OPERATORS AT THE SAME TIME

OPERATOIRES	VACUUM MODULES	DUST SEPARATORS
3	T30INV	100/B - 100/B-AP
4	T40INV	100/B - 100/B-AP
6	T60INV	150/A - 150/A-AP

### ELECTRIC AND HYDRAULIC CONNECTION

- 1 - Vacuum model
- 2 - Dust separator
- 3 - Dust inlet line
- 4 - Socket frame
- 5 - 12V power supply line
- 6 - ON/OFF switch
- 7 - Air inlet line
- 8 - Air exhaust line
- 9 - Metallic silencer

